Installation Ubuntu 18.04 Server

An dieser Stelle ist das Basis-Setup bereits durchgeführt.

Netzwerkkonfiguration

Ubuntu 18.04 nutzt den Netzwerkmanager „netplan“ statt des alten Pakets „ifupdown“. Ich lege jedoch die `/etc/network/interfaces` an, da ich später netplan wieder gegen ifupdown tauschen werde.

/etc/network/interfaces

```
auto lo
iface lo inet loopback

auto ens3
iface ens3 inet static
address 192.168.39.32
netmask 255.255.255.0
gateway 192.168.39.1
dns-nameservers 9.9.9.9
```

Der erste Abschnitt der Datei aktiviert das Loopback-Interface für Verbindungen über 127.x.x.x. Der zweite Abschnitt konfiguriert die Netzwerkkarte des Systems. Mit dem Konfigurationsbefehl `auto` wird erreicht, dass das Interface beim booten automatisch aktiviert wird.

Reaktivierung von ifupdown

Um netplan zu deaktivieren / deinstallieren, muss lediglich das Paket ifupdown installiert werden:

```
aptitude install ifupdown
```

Im Bootloader muss ebenfalls das Laden von netplan unterdrückt werden:

/etc/default/grub

```
[...]
GRUB_CMDLINE_LINUX="netcfg/do_not_use_netplan=true"
```

```
update-grub
```

Um das klassische Verhalten von ifupdown wiederherzustellen, muss ebenfalls systemd-networkd

ausgeschaltet werden. Dies geschieht folgendermaßen:

```
systemctl disable systemd-networkd.service
systemctl mask systemd-networkd.service
systemctl stop systemd-networkd.service
```

Die Netzwerkkonfiguration sollte nun komplett aus der interfaces-Datei übernommen werden. Eine Ausnahme stellen die DNS-Server dar. Damit diese ebenfalls aus interfaces übernommen werden, muss systemd-resolved ausgeschaltet und resolvconf aktiviert werden!

```
aptitude install resolvconf
```

```
systemctl disable systemd-resolved.service
systemctl stop systemd-resolved.service
systemctl mask systemd-resolved.service
```

```
reboot
```

NTP Client

/etc/systemd/timesyncd.conf

```
#  This file is part of systemd.
#
#  systemd is free software; you can redistribute it and/or modify it
#  under the terms of the GNU Lesser General Public License as
published by
#  the Free Software Foundation; either version 2.1 of the License, or
#  (at your option) any later version.
#
# Entries in this file show the compile time defaults.
# You can change settings by editing this file.
# Defaults can be restored by simply deleting this file.
#
# See timesyncd.conf(5) for details.

[Time]
NTP=ptbtime1.ptb.de
FallbackNTP=ptbtime3.ptb.de ptbtime2.ptb.de
```

Momentane Systemzeit ansehen:

```
timedatectl
```

```
                      Local time: So 2018-11-25 11:26:59 CET
                  Universal time: So 2018-11-25 10:26:59 UTC
                        RTC time: So 2018-11-25 10:27:00
```

```
                      Time zone: Europe/Berlin (CET, +0100)
      System clock synchronized: yes
systemd-timesyncd.service active: yes
                RTC in local TZ: no
```

```
systemctl restart  systemd-timesyncd
systemctl status  systemd-timesyncd
● systemd-timesyncd.service - Network Time Synchronization
   Loaded: loaded (/lib/systemd/system/systemd-timesyncd.service; enabled;
vendor preset: enabled)
   Active: active (running) since Sun 2018-11-25 11:29:00 CET; 1s ago
     Docs: man:systemd-timesyncd.service(8)
 Main PID: 16475 (systemd-timesyn)
   Status: "Synchronized to time server 192.53.103.108:123
(ptbtime1.ptb.de)."
    Tasks: 2 (limit: 2319)
   CGroup: /system.slice/systemd-timesyncd.service
           └─16475 /lib/systemd/systemd-timesyncd


Nov 25 11:29:00 backup systemd[1]: Starting Network Time Synchronization...
Nov 25 11:29:00 backup systemd[1]: Started Network Time Synchronization.
Nov 25 11:29:01 backup systemd-timesyncd[16475]: Synchronized to time server
192.53.103.108:123 (ptbtime1.ptb.de).
```

"Mini" Postfix


Der MTA Postfix soll nur dazu dienen Mails zu versenden. So können Informationen, zum Beispiel an den Admin, vom System versendet werden oder Webseiten können mit Ihren Benutzern kommunizieren, wenn beispielsweise ein Passwort zurückgesetzt werden soll.

Zunächst sind die benötigten Pakete zu installieren.

```
aptitude install postfix
Die folgenden NEUEN Pakete werden zusätzlich installiert:
  postfix ssl-cert{a}
0 Pakete aktualisiert, 2 zusätzlich installiert, 0 werden entfernt und 8
nicht aktualisiert.
1.164 kB an Archiven müssen heruntergeladen werden. Nach dem Entpacken
werden 4.141 kB zusätzlich belegt sein.
Möchten Sie fortsetzen? [Y/n/?]
```



Hier die Default-Maildomäne eintragen:



Folgende Konfigurationsparameter anpassen:

/etc/postfix/main.cf

```
smtp_generic_maps = hash:/etc/postfix/generic
mydestination = $myhostname, myhostname.mydomain.de, localhost
inet_interfaces = loopback-only
inet_protocols = ipv4
relayhost =  [smtp.myprovider.de]
```

/etc/postfix/generic

```
root@myhostname.mydomain.de                 something@mydomain.de
@myhostname.mydomain.de                     @mydomain.de
```

/etc/aliases

```
# See man 5 aliases for format
postmaster:    root
root:   something@mydomain.de
```

Die Konfigurationen anwenden:

```
postmap hash:/etc/postfix/generic
newaliases
service postfix restart
```

Apticron

Installation

```
apt-get update
aptitude install apticron
vi /etc/apticron/apticron.conf
```

Konfiguration

Gegebenenfalls sollte hier die Empfängeradresse angepasst werden:

/etc/apticron/apticron.conf

```
# apticron.conf
#
# The values set in /etc/apticron/apticron.conf will override the
settings
# in this file.

#
# Set EMAIL to a space separated list of addresses which will be
notified of
# impending updates. By default the root account will be notified.
#
EMAIL="root"
[...]
```

Scheduled Task

Wann Apticron ausgeführt wird, kann über Cron angepasst werden:

```
vi /etc/cron.d/apticron
```

From:
https://wiki.sebastianhetzel.net/ - **Sebastians IT-Wiki**

Permanent link:
https://wiki.sebastianhetzel.net/ubuntu:18-04_server_install?rev=1549572205

Last update: **2019/02/07 20:43**